

TCE1000

Our entry-level 2 door upright glass door fridge

For a great value General Display fridge, look no further than the TCE1000 with EZICORE - a convenient & easy to remove refrigeration cartridge.

Quick Guide

| Display & Store | \odot |
|------------------------------------|----------|
| Food & Drinks (M1 rating) | Ø |
| EZICORE - easy to remove cartridge | Ø |
| Ambient temperature rated 35°C | Ø |
| LED Internal Lighting | Ø |
| 1 year Warranty Protection | Ø |

















Restaurants / Restaurants Cafés

Convenience **Stores**

Venues

Accommodation

Clubs / Pubs /

Schools





Specifications TCE1000

| | 2 Glass Door |
|--|---|
| External | Integral |
| Туре | Fridge |
| Dimensions (W x D x H mm) | 1130 X 750 X 2200 |
| Total floor area (m²) | 0.85 |
| Weight (kg) | TBC |
| Door (safety glass) | 2 |
| Door Design | Plastic frame & double glazed |
| Controller | Electronic |
| Remote available | No |
| Remote duty (Watts -5°C SST) | N/A |
| Breathes from / Expels air to | Upper front / Top |
| Sign | Illuminated sign panel |
| Cabinet construction | Powder coated steel |
| Drainage (plumbing required) | No |
| Internal | |
| Gross volume (litres) | 980 |
| Lighting (vertical LED light) | 2 (on the door) |
| No. of shelves (per door) | 4 |
| Shelf design | White plastic-coated wire |
| Total shelf area (m²) | 1.91 |
| Product facings (600ml PET bottle) | 70 |
| Total product loading | 420 PETs |
| Coil coating | TBC |
| Compressor | Embraco FFI12HBK |
| Performance | |
| MEPS category | M1 (food & drinks) |
| MEPS efficiency (kWh/24h/m²) @ Climate Class 3 | 6.7 |
| Temperature range (adjustable up to 15°C) | o°C to 5°C |
| TEC (kWh/24h) @ Climate Class 3 | 7.5 (new modified number) |
| High efficiency model | Yes |
| Maximum ambient temperature* | 35°C |
| Maximum Climate Class rating | 4 |
| Refrigeration system | Ezicore removable cartridge |
| Refrigerant / Charge | R134a / 270g |
| Total display area (m²) | 1.09 |
| Glass dew point | TBC |
| Decibel rating | 60.2dB(A) |
| Electrical | |
| Electrical power (kW) | 0.733 |
| Current draw (Amps) | 3 |
| 10 Amp 3 pin plug | Yes |
| Controller & temp display | Electronic |
| Light switch on controller | Light switch for internal light & light box |