

BPG135 BRATT PAN



BPG135 standard features and benefits

- Nominal capacity of 135 litre stainless steel pan
- · Smooth stainless steel exterior
- Seven powerful burners located in the base of the pan, together with 10 mm thick Duplex seamless stainless steel base provides improved heat retention, even heat and ease of cleaning
- · Ergonomically designed counter balanced, screwless double skin lid with heavy duty lifting mechanism and drip zone at the back
- Simple high to low flame adjustable control
- · Pan design with a rounded corners and no edges
- · Wide opening for unloading and easy cleaning
- Pouring spout
- · Heavy duty electronic tilt mechanism
- ¼ turn tap and fixed spout on top
- · Battery operated spark ignition
- · Safety gas cut off valve
- · Pilot flame failure
- All components easily serviceable from the front
- · All new sleek design

Standard accessories

Adjustable legs 140-170 mm

Optional accessories part codes

50-300 °C thermostatic

burner control

C2 100 mm castors set of 2 C4 100 mm castors set of 4,

2 with brakes

for use with castors **CHAIN**















Please note, due to ongoing product development and improvement, we reserve the right to change product design and specification at any time without notice







BPG135 BRATT PAN









3/4" BSP Gas Inlet 10 AMP/230V Plug with 3m Lead Cable − 1/2" Quick Connect Water Inlet



BPG135 SPECIFICATIONS

| Dimensions (WxDxH) | 995 x 905 x 1070 mm |
|--------------------|---------------------|
| Tank size (WxDxH) | 895 x 670 x 310 mm |
| Nominal capacity | 135 L |

| Gas connection | BSP 3/4" M |
|-----------------------|------------------|
| Rating NG/LPG | 120 / 100 MJ |
| Electrical connection | 10 AMP/230V Plug |

INSTALLATION CLEARANCES (minimum)

| Front | 400 mm |
|-------|--------|
| Floor | 150 mm |

| Combustible | Side | 100 mm |
|-------------|------|--------|
| Material | Rear | 100 mm |

| Non-combustible | Side | 0 mm |
|-----------------|------|------|
| Material | Rear | 0 mm |

Please note, due to ongoing product development and improvement, we reserve the right to change product design and specification at any time without notice

