


specifications

RF7.PPS.3.SD

ReFlex Series, 3 Solid Door, Medium Salad Preparation Fridge

Project: _____

Item No: _____



CABINET	
Doors	3 × self-closing, lockable, solid swing doors with stay-open position at over 90°, hinged LH, LH, RH
Internal door opening	3 × door openings: 590 mm high × 370 mm wide
Shelves	6 × adjustable height shelves. Middle shelves: 475 mm wide × 510 mm deep. Outer shelves: 415 mm wide × 510 mm deep. Each shelf is held in place with 4 × shelf clips. Additional shelf clips are available on request.
Worktop	Removable, food grade, 13 mm plastic cutting board
Material	304 AISI stainless steel interior and exterior
PERFORMANCE	
Max. ambient temperature	40°C (lid(s) closed), or 30°C (lid(s) open)
Temperature range	1°C to 5°C (adjustable with SKOPE-connect™ -2°C to 15°C)
Total energy consumption	3.58 kWh/24 h (@ 30°C/55% relative humidity)
Annual running cost	\$392 p.a. (@ \$0.30/kWh)
ELECTRICAL	
Electrical safety climate class	5 (40°C/40% relative humidity)
Interior lighting	2 × 400 mm, 4W LED lights (door activated)
Power cord	Supplied with a 10 amp plug and 2 m lead
Power supply	220-240 volts a.c. 50 Hz, single phase supply
Current draw	2.0 amps (includes unit 1.0 amps)
REFRIGERATION	
Controller	SCS Connect (SKOPE-connect™ compatible)
Connectivity interface	Bluetooth wireless technology
Refrigeration system	Side-mounted, integral, removable refrigeration cartridge (part number ULQCNI-0029)
Refrigerant	R290/90 g (natural refrigerant)
Nominal capacity	600 watts
Heat rejection (avg./peak)	150 watts/160 watts
Drainage	No plumbing required in standard applications. If lids are left open for more than 4 hours per day, or venues have high or fluctuating ambient temperatures and humidity, SKOPE recommends connecting condensate to an in-floor drain.

DIMENSIONS		
	External	Internal
Height	1110 mm	490 mm
Width	1800 mm	1350 mm
Depth	700 mm	540 mm
Floor area	1.26 m ²	
Weight	162 kg	
Gross volume	357 L	

Height variation	
Supplied castors	1110 mm
Height adjustable legs	1120 to 1170 mm
No castors	975 mm

Dimensional tolerances		
Before installing this cabinet allow the following dimensional tolerances:		
Linear dimensions	Overall cabinet dimensions	
Less than 1 metre	±5 mm	
More than 1 metre	-5 mm to +10 mm	
	Length of multiple cabinets	
	At each joint	At each end wall
Less than 1 metre	±5 mm	+15 mm
More than 1 metre	-5 mm to +10 mm	+15 mm

Ventilation requirements	
Top	Not required
Sides	Not required
Back	Not required
Bottom	Not required