

VERTICAL DISPLAY & STORAGE

Fan Forced Freezers

- Internal bright light promotes impulse sales
- Illuminated advertising display lightbox
- Corrosion resistant outer body
- Door mechanism stationary opened makes it easier to place and take out products
- 5 tier removable and adjustable shelves
- Self contained system, no plumbing required
- Electrically heated glass door with on/off switch.
- Automatic defrost system, saves energy consumption and provide shortest possible defrost cycle
- High density cyclo-isopentane polyurethane insulated body saves energy



Glass Door Fan Forced Freezer
W/ Lightbox 444L LED
UF0500LF



Glass Door Fan Forced Freezer
W/ Lightbox 976L LED
UF1000LF



Glass Door Fan Forced Freezer
W/ Lightbox 1507L LED
UF1500LF

	UF0500LF	UF1000LF	UF1500LF
Bromic Part Number	3736220	3736221	3736222
Capacity - Gross (litres)	406L	893L	1378L
External Dimensions (mm) <small>Depth dimensions exclude lightbox and handle protrusions</small>	635w x 760d x 2060h	1260w x 760d x 2060h	1880w x 760d x 2060h
Internal Dimensions (mm)	520w x 550d x 1420h	1143w x 550d x 1420h	1755w x 595d x 1435h
Temperature range (°C)	-18 to -22°C	-18 to -22°C	-18 to -22°C
Max. ambient temp °C/RH%	32°C/60%	32°C/60%	32°C/60%
Refrigeration Power (Watts)	1000W	1600W	2000W
Current (Amps)	4.7A	8A	15A
Plug Supplied	Yes, 10amp	Yes, 15amp	Yes, 15amp
Light Display Box	Yes	Yes	Yes
Interior light	LED	LED	LED
No. Of Doors	1 Non Reversible	2	3
Door Material	Double Glazed Thermo Glass	Double Glazed Thermo Glass	Double Glazed Thermo Glass
Door Lock	No	No	No
Temperature controller	Digital	Digital	Digital
Number of shelves	5 + Base	5 + 5 + Base	5 + 5 + 5 + Base
Gross weight (kg)	113Kg	199Kg	279Kg
Refrigerant	R404a	R404a	R404a
Colour	White With S/Steel Trim	White With S/Steel Trim	White With S/Steel Trim
Power Usage (at 30 °C/60%RH)	15.25KWh/24hr	21.54KWh/24hr	32.89KWh/24hr



Danfoss



WARRANTY 1 YR PARTS
YR LABOUR